

NORTON





SAINT-GOBAIN






clipper[®]

MASONRY SAWS



MASONRY SAWS

 <p>Ø350 mm 110mm MAX CUT DEPTH 130mm MAX MATERIAL HEIGHT</p> <p>ELECTRIC 3HP 2kW</p> <p>CST120 UNO</p>	 <p>Ø350 mm 110mm MAX CUT DEPTH 130mm MAX MATERIAL HEIGHT</p> <p>ELECTRIC 3HP 2,2kW</p> <p>CST100/120</p>	 <p>Ø350 mm 110mm MAX CUT DEPTH 195mm MAX MATERIAL HEIGHT</p> <p>ELECTRIC 3HP 2,2kW</p> <p>CST 150</p>	 <p>Ø400 mm 150mm MAX CUT DEPTH 280mm MAX MATERIAL HEIGHT</p> <p>ELECTRIC/PETROL* 3HP 2,2kW 4HP 3kW 6,5HP* 4,8kW*</p> <p>CM401</p>
---	---	---	--

 <p>Ø500 mm 195mm MAX CUT DEPTH 355mm MAX MATERIAL HEIGHT</p> <p>ELECTRIC / PETROL* 5,5HP 4,0kW 6,5HP* 4,8kW*</p> <p>CM501</p>	 <p>Ø500 mm 190mm MAX CUT DEPTH 355mm MAX MATERIAL HEIGHT</p> <p>ELECTRIC 7,5HP 5,5kW</p> <p>ISM/ISC</p>	 <p>Ø650 mm 265mm MAX CUT DEPTH 280mm MAX MATERIAL HEIGHT</p> <p>ELECTRIC / PETROL* 3HP 2,2kW 6,5HP 4,8kW 7,5HP* 5,5kW*</p> <p>JUMBO 651</p>	 <p>Ø900/1000** mm 370/420** mm MAX CUT DEPTH 440mm MAX MATERIAL HEIGHT</p> <p>ELECTRIC / PETROL* 10HP 7,5W 13HP* 9,6kW*</p> <p>JUMBO 900/1000</p>	 <p>508mm MAX CUT DEPTH 508mm MAX MATERIAL HEIGHT</p> <p>ELECTRIC 2,5HP 1,85kW</p> <p>CB511</p>
--	--	--	---	---




CM501 MAJOR

FEATURES

- Conveyor cart with anti-slipping surface
- Easy access to water pump
- Double lifting rails
- Blade adjustment with crank

BENEFITS

- Accurate and stable cut
- Easy maintenance
- Easy and safe transport with forklift
- Easy and accurate blade depth setting




Item No	701846 27018	701846 28233	701846 27020	701846 28232 *
EAN 13 Code	5450248 371762	5450248 392101	5450248 371779	5450248 392095
Engine type	Electric	Electric	Petrol - Honda GX200	Electric
Supply Voltage/ Power kW	400V / 4kW (5,5 HP)	230-400V-3 / 4kW (5,5 HP)	4,8kW (6,5 HP)	400V / 4kW / (5,5 HP)
Blade x bore (mm)	Ø 500x25,4	Ø 500x25,4	Ø 500x25,4	Ø 600x25,4
Tool speed RPM	1900 min-1	1900 min-1	2200 min-1	1900 min-1
Max. cutting depth at 90° / 45° (mm)	195	195	195	245
Max. cutting length (mm)	500	500	500	500
Max. material height (mm)	355	355	355	355
Table size (mm)	580 x 420	580 x 420	580 x 420	580 x 420
Hand Arm Vibrations	< 2,5 m/s ²	< 2,5 m/s ²	< 2,5 m/s ²	< 2,5 m/s ²
Sound power / pressure level	97dB(A) / 81dB(A)	97dB(A) / 81dB(A)	106dB(A) / 93dB(A)	97dB(A) / 81dB(A)
Dimensions (LxWxH) (mm)	1480x610x1550	1480x610x1550	1480x610x1700	1480x610x1550
Weight	165kg	163kg	165kg	168kg

PRODUCT FEATURES



MAX CUT DEPTH - Ø500



CUTTING GUIDE



FRICTION RESISTANT TILTED ROLLERS



MAX CUT DEPTH - Ø600

DIAMOND BLADE RECOMMENDATIONS FOR CM501

Substrate / Material	BETON	SILENCIO	UNIVERSAL	REFRACTORY	ALL MATERIALS
Recommended Product	PRO BETON	EXTREME UNI SILENCIO	EXTREME UNIVERSAL		PRO 4X4 EXPLORER
Bore (mm)	25,4	25,4	25,4		25,4
Ø500mm Item No.	701846 27064	701846 30309	701846 11440	SEE RECOMMENDATION TABLE PAGE 52	701846 02097
Ø600mm Item No.	701846 27065	-	-		-
Page reference	20	27	26		36